Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision Date: 08/21/2023 Date of Issue: 08/21/2023

#### SECTION 1: IDENTIFICATION

#### 1.1. Product Identifier

Product Form: Mixture

Product Name: Magic Wrinkle Releaser

Product Code: 38206

Synonyms: Wrinkle Remover

\*This document is intended to be used for safety in the workplace only, and is not a consumer document.

#### **1.2.** Intended Use of the Product

Fabric wrinkle releaser

#### 1.3. Name, Address, and Telephone of the Responsible Party

Faultless Brands 1025 W 8th St. Kansas City, MO 64101 USA T: 1-816-842-1230

#### www.faultless.com

**1.4.** Emergency Telephone Number Emergency Number : 1-800-424-9300 (CHEMTREC)

#### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1. Classification of the Substance or Mixture

#### **GHS-US Classification**

Gases Under Pressure - Liquefied gas- H280

Eye Irrit. 2A H319

Full text of hazard classes and H-statements : see section 16

#### 2.2. Label Elements

#### GHS-US Labeling

Hazard Pictograms (GHS-US)



Signal Word (GHS-US) Hazard Statements (GHS-US)	<ul> <li>Warning</li> <li>H280 - Contains gas under pressure; may explode if heated.</li> <li>H319 - Causes serious eye irritation.</li> </ul>
Precautionary Statements (GHS-US)	<ul> <li>P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.</li> <li>P280 - Wear protective gloves, protective clothing, and eye protection.</li> <li>P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</li> <li>P337+P313 - If eye irritation persists: Get medical advice/attention.</li> <li>P410+P403 - Protect from sunlight. Store in a well-ventilated place.</li> </ul>

#### 2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions. Contact with gas escaping the container can cause frostbite. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

2.4. Unknown Acute Toxicity (GHS-US) No data available

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS 3.1. Substances

Not applicable **3.2. Mixture** 

Name	Product Identifier	% (w/w)
Ethyl alcohol	(CAS No) 64-17-5	7 - 13

Version: 4.0

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Petroleum gases, liquefied, sweetened	(CAS No) 68476-86-8	3 - 7
Polyethylene glycol	(CAS No) 25322-68-3	0.1 - 1
Sodium nitrite	(CAS No) 7632-00-0	0.1-0.2
Morpholine	(CAS No) 110-91-8	< 0.1
Citral	(CAS No) 5392-40-5	< 0.1

#### SECTION 4: FIRST AID MEASURES

#### 4.1. Description of First-aid Measures

**General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). If frostbite or freezing occurs, immediately flush with plenty of lukewarm water to GENTLY warm the affected area. Do not use hot water. Do not rub affected area. Get immediate medical attention.

**Inhalation:** When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

**Skin Contact:** Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Obtain medical attention if irritation develops or persists. Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

**Eye Contact:** Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

#### 4.2. Most Important Symptoms and Effects Both Acute and Delayed

General: May cause frostbite on contact with the liquid. Causes serious eye irritation.

**Inhalation**: Prolonged exposure may cause irritation. Contains a small amount of gases that are simple asphyxiants. If a large amount of gas is released in a confined space, gas could be toxic as a simple asphyxiant by displacing oxygen from the air.

Skin Contact: Contact with gas/liquid escaping the container can cause frostbite and freeze burns.

**Eye Contact**: Contact with gas/liquid escaping the container can cause frostbite, freeze burns, and permanent eye damage. Contact causes severe irritation with redness and swelling of the conjunctiva.

**Ingestion:** Not considered a potential route of exposure, but contact with gas/liquid escaping the container can cause freeze burns and frostbite.

Chronic Symptoms: None known.

#### 4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

#### **SECTION 5: FIRE-FIGHTING MEASURES**

#### 5.1. Extinguishing Media

**Suitable Extinguishing Media:** Water spray, dry chemical, foam, carbon dioxide. Water may be ineffective but water should be used to keep fire-exposed container cool.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

#### 5.2. Special Hazards Arising From the Substance or Mixture

**Fire Hazard:** In accordance with subsections 31.4 and 31.5 of the UN Recommendations on the Transport of Dangerous Goods, Manual of Tests and Criteria, for Ignition distance test, and Enclosed space ignition test this material is not classified as a flammable aerosol.

**Explosion Hazard:** Container may explode in heat of fire.

Reactivity: Hazardous reactions will not occur under normal conditions.

#### 5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

**Firefighting Instructions:** Remove containers from fire area if this can be done without risk. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion. Use water spray or fog for cooling exposed containers. Fight fire remotely due to the risk of explosion.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection. **Hazardous Combustion Products**: Thermal decomposition generates: Carbon oxides (CO, CO<sub>2</sub>). Nitrogen oxides. Sulfur oxides. Sodium oxides. Hydrocarbons.

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### **Reference to Other Sections**

Refer to Section 9 for flammability properties.

#### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### 6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Avoid breathing (vapor, mist, spray). Avoid all contact with skin, eyes, or clothing.

#### 6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

#### 6.1.2. For Emergency Personnel

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedures:** Ventilate area. Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

#### 6.2. Environmental Precautions

Prevent entry to sewers and public waters.

#### 6.3. Methods and Materials for Containment and Cleaning Up

**For Containment:** Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. As an immediate precautionary measure, isolate spill or leak area in all directions.

**Methods for Cleaning Up:** Clean up spills immediately and dispose of waste safely. Stop the source of the release, if safe to do so. Consider the use of water spray to disperse vapors. Isolate the area until gas has dispersed. Absorb and/or contain spill with inert material. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

#### 6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

#### **SECTION 7: HANDLING AND STORAGE**

#### 7.1. Precautions for Safe Handling

Additional Hazards When Processed: Do not pressurize, cut, or weld containers. Ruptured cylinders may rocket.

**Precautions for Safe Handling:** Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid breathing vapors, mist, and spray. Avoid contact with skin, eyes and clothing.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

#### 7.2. Conditions for Safe Storage, Including Any Incompatibilities

**Technical Measures:** Comply with applicable regulations. Proper grounding procedures to avoid static electricity should be followed. **Storage Conditions:** Keep only in original container. Keep container closed when not in use. Store in a dry, cool and well-ventilated place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

**Incompatible Products:** Strong acids, strong bases, strong oxidizers. Halogenated hydrocarbons. Nitrogen oxides. Fluorinated compounds. Metal Catalysts.

#### 7.3. Specific End Use(s)

Fabric wrinkle releaser

#### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), or OSHA (PEL).

Ethyl alcohol (64-17-5)				
USA ACGIH	ACGIH STEL (ppm)	1000 ppm		
USA ACGIH	ACGIH chemical category Confirmed Animal Carcinogen with Unknown Relevance			
		Humans		
USA OSHA	OSHA PEL (TWA) (mg/m³)	1900 mg/m <sup>3</sup>		
USA OSHA	OSHA PEL (TWA) (ppm)	1000 ppm		
USA NIOSH	NIOSH REL (TWA) (mg/m³)	1900 mg/m <sup>3</sup>		
USA NIOSH	NIOSH REL (TWA) (ppm)	1000 ppm		

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

USA IDLH	US IDLH (ppm)	3300 ppm (10% LEL)			
Polyethylene glycol (25322-68-3)					
USA AIHA	WEEL TWA (mg/m³)	10 mg/m <sup>3</sup> (MW>200, aerosol)			
Morpholine (110-91-8)					
USA ACGIH	ACGIH TWA (ppm)	20 ppm			
USA ACGIH	ACGIH chemical category	Skin - potential significant contribution to overall exposure			
		by the cutaneous route, Not Classifiable as a Human			
		Carcinogen			
USA OSHA	OSHA PEL (TWA) (mg/m³)	70 mg/m <sup>3</sup>			
USA OSHA	OSHA PEL (TWA) (ppm)	20 ppm			
USA OSHA	Limit value category (OSHA)	prevent or reduce skin absorption			
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	70 mg/m <sup>3</sup>			
USA NIOSH	NIOSH REL (TWA) (ppm)	20 ppm			
USA NIOSH	NIOSH REL (STEL) (mg/m <sup>3</sup> )	105 mg/m <sup>3</sup>			
USA NIOSH	NIOSH REL (STEL) (ppm)	30 ppm			
USA IDLH	US IDLH (ppm) 1400 ppm (10% LEL)				
Citral (5392-40-5)					
USA ACGIH	ACGIH TWA (ppm)	5 ppm (inhalable fraction and vapor)			
USA ACGIH	ACGIH chemical category	dermal sensitizer, Skin - potential significant contribution to			
		overall exposure by the cutaneous route, Not Classifiable			
		as a Human Carcinogen			

#### 8.2. Exposure Controls

**Appropriate Engineering Controls**: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Use explosion-proof equipment. Ensure all national/local regulations are observed.

Personal Protective Equipment: Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.



Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear protective gloves. If material is cold, wear thermally resistant protective gloves.

Eye Protection: Chemical safety goggles.

Skin and Body Protection: Wear suitable protective clothing.

**Respiratory Protection**: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

Thermal Hazard Protection: Wear thermally resistant protective clothing.

#### Other Information: When using, do not eat, drink or smoke.

#### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1. Information on Basic Physical and Chemical Properties

Physical State	:	Liquid
Appearance	:	Clear to hazy aerosol
Odor	:	Not available
Odor Threshold	:	Not available
рН	:	9 - 10
Evaporation Rate	:	Not available
Melting Point	:	Not available
Freezing Point	:	Not available

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

According to rederal Register / vol. 77, No. 58 / Wolfday, March 26, 2012 / Rules and Regulations				
Boiling Point	:	182 °F (83.33 °C)		
Flash Point	:	134 °F (56.67 °C)		
Auto-ignition Temperature	:	Not available		
Decomposition Temperature	:	Not available		
Flammability (solid, gas)	:	Not available		
Lower Flammable Limit	:	Not available		
Upper Flammable Limit	:	Not available		
Vapor Pressure	:	Not available		
Relative Vapor Density at 20°C	:	Not available		
Relative Density	:	Not available		
Specific Gravity	:	0.98 g/ml		
Solubility	:	Not available		
Partition Coefficient: N-Octanol/Water	:	Not available		
Viscosity	:	Not available		
Explosive Properties	:	Contains gas under pressure; may explode if heated		
Explosion Data - Sensitivity to Mechanical Impact	:	Not expected to present an explosion hazard due to mechanical impact.		
Explosion Data - Sensitivity to Static Discharge	:	Not expected to present an explosion hazard due to static discharge.		

#### **SECTION 10: STABILITY AND REACTIVITY**

**10.1. Reactivity:** Hazardous reactions will not occur under normal conditions.

**10.2.** Chemical Stability: Contains gas under pressure; may explode if heated.

**10.3.** Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

**10.4.** Conditions to Avoid: Direct sunlight, extremely high or low temperatures, open flames, sources of ignition and incompatible materials.

**10.5.** Incompatible Materials: Strong acids, strong bases, strong oxidizers. Halogenated hydrocarbons. Nitrogen oxides. Fluorinated compounds. Metal Catalysts.

**10.6.** Hazardous Decomposition Products: None known.

#### SECTION 11: TOXICOLOGICAL INFORMATION

#### 11.1. Information on Toxicological Effects - Product

Acute Toxicity: Not classified

LD50 and LC50 Data: Not available

Skin Corrosion/Irritation: Not classified

**pH:** 9 - 10

Serious Eye Damage/Irritation: Causes serious eye irritation.

**pH:** 9 - 10

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Teratogenicity: Not classified

Carcinogenicity: Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified

**Symptoms/Injuries After Inhalation:** Prolonged exposure may cause irritation. Contains a small amount of gases that are simple asphyxiants. If a large amount of gas is released in a confined space, gas could be toxic as a simple asphyxiant by displacing oxygen from the air.

Symptoms/Injuries After Skin Contact: Contact with gas/liquid escaping the container can cause frostbite and freeze burns. Symptoms/Injuries After Eye Contact: Contact with gas/liquid escaping the container can cause frostbite, freeze burns, and permanent eye damage. Contact causes severe irritation with redness and swelling of the conjunctiva.

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/Injuries After Ingestion: Not considered a potential route of exposure, but contact with gas/liquid escaping the container can cause freeze burns and frostbite.

Chronic Symptoms: None known.

#### Information on Toxicological Effects - Ingredient(s) 11.2.

LD50 and LC50 Data:

Ethyl alcohol (64-17-5)	
LD50 Oral Rat	10470 mg/kg
LD50 Dermal Rat	20 ml/kg
LC50 Inhalation Rat	124.7 mg/l/4h
Polyethylene glycol (25322-68-3)	
LD50 Oral Rat	47000 mg/kg
LD50 Dermal Rabbit	> 20 ml/kg
Sodium nitrite (7632-00-0)	
LD50 Oral Rat	85 mg/kg
LC50 Inhalation Rat	5.5 mg/l/4h
Morpholine (110-91-8)	
LD50 Oral Rat	1050 mg/kg
LD50 Dermal Rabbit	1900 mg/kg
LC50 Inhalation Rat	24 mg/l/4h
LC50 Inhalation Rat	8000 ppm (Exposure time: 8 h)
ATE (Vapors)	11.00 mg/l/4h
Citral (5392-40-5)	
LD50 Oral Rat	4960 mg/kg
LD50 Dermal Rabbit	2250 mg/kg
Ethyl alcohol (64-17-5)	
IARC Group	1
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.
Morpholine (110-91-8)	
IARC Group	3
SECTION 12: ECOLOGICAL INFORMATION	

#### SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General: Not classified.

# Ethyl alcohol (64-17-5)

EC50 Daphnia 1	9268 - 14221 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
LC50 Fish 2	> 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])	
ErC50 (algae)	1000 mg/l	
Sodium nitrite (7632-00-0)		
LC50 Fish 1	0.19 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])	
LC50 Fish 2	0.092 - 0.13 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])	
Morpholine (110-91-8)		
LC50 Fish 1	350 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])	
LC50 Fish 2	375 - 460 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)	
ErC50 (algae)	28 mg/l	
Citral (5392-40-5)		
LC50 Fish 1	4.1 mg/l	
C50 Daphnia 1 7 mg/l (Exposure time: 48 h - Species: Daphnia magna)		
12.2. Persistence and Degradability		

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Magic Wrinkle Releaser			
Persistence and Degradability	Not established.		
Ethyl alcohol (64-17-5)			
Persistence and Degradability	Readily biodegradable.		
12.3. Bioaccumulative Potential			
Magic Wrinkle Releaser			
Bioaccumulative Potential	Not established.		
Ethyl alcohol (64-17-5)			
Log Pow	-0.32		
Bioaccumulative Potential	Not established.		
Sodium nitrite (7632-00-0)			
Log Pow	-3.7 (at 25 °C)		
Morpholine (110-91-8)			
BCF Fish 1	0.3 - 2.8		
Log Pow	-2.55 (at 25 °C)		
Citral (5392-40-5)			
<b>Log Pow</b> 2.76 (at 25 °C)			
Petroleum gases, liquefied, sweetened (68476-86-8)			
Log Pow	<= 2.8		

**12.4. Mobility in Soil** Not available

#### 12.5. Other Adverse Effects

**Other Information:** Avoid release to the environment.

### SECTION 13: DISPOSAL CONSIDERATIONS

#### **13.1.** Waste treatment methods

**Waste Disposal Recommendations:** Dispose of contents/container in accordance with local, regional, national, and international regulations.

Additional Information: Container may remain hazardous when empty. Continue to observe all precautions. Do not puncture or incinerate container.

Ecology - Waste Materials: Avoid release to the environment.

### SECTION 14: TRANSPORT INFORMATION

14.1. In Accordance v	vith DOI		
Proper Shipping Name	: AEROSOLS non-flammable, (ea	ach not exceeding 1 L capacity)	
Hazard Class	: 2.2		
Identification Number	: UN1950	$\frown$	
Label Codes	: 2.2	$\checkmark$	
ERG Number	: 126		

Shipped under 49 CFR, Packaging Exception 173.306 - Consumer Commodities, Limited Quantities of Compressed Gases

#### 14.2. In Accordance with IMDG

Proper Shipping Name	: AEROSOLS non-flammable, (eac	h not exceeding 1 L capacity)
Hazard Class	: 2	
Division	: 2.2	
Identification Number	: UN1950	
Label Codes	: 2.2	
EmS-No. (Fire)	: F-D	$\frown$
EmS-No. (Spillage)	: S-U	$\checkmark$

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

14.3. In Accordance with IATA		
Proper Shipping Name	: AEROSOLS, NON-FLAMMABLE , (each not exceeding 1 L capacity)	
Identification Number	: UN1950	
Hazard Class	: 2 ( Y )	
Label Codes	: 2.2	
Division	: 2.2	
ERG Code (IATA)	: 2L	

### SECTION 15: REGULATORY INFORMATION

15.1. US Federal Regulations

Magic Wrinkle Releaser			
SARA Section 311/312 Hazard Classes	Sudden release of pressure hazard		
	Immediate (acute) health hazard		
Ethyl alcohol (64-17-5)			
Listed on the United States TSCA (Toxic Substances Control Act	) inventory		
Polyethylene glycol (25322-68-3)			
Listed on the United States TSCA (Toxic Substances Control Act) inventory			
Sodium nitrite (7632-00-0)			
Listed on the United States TSCA (Toxic Substances Control Act	) inventory		
Subject to reporting requirements of United States SARA Section 313			
EPA TSCA Regulatory Flag	S - S - indicates a substance that is identified in a proposed or final		
	Significant New Uses Rule		
SARA Section 313 - Emission Reporting	1.0 %		
Morpholine (110-91-8)			
Listed on the United States TSCA (Toxic Substances Control Act) inventory			
Citral (5392-40-5)			
Listed on the United States TSCA (Toxic Substances Control Act) inventory			
Petroleum gases, liquefied, sweetened (68476-86-8)			
Listed on the United States TSCA (Toxic Substances Control Act) inventory			
15.2. US State Regulations			
Ethyl alcohol (64-17-5)			
U.S California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of		
	California to cause cancer. Ethyl Alcohol is included on the		
	Proposition 65 list when it is used in alcoholic beverages.		
U.S California - Proposition 65 - Developmental Toxicity	WARNING: This product contains chemicals known to the State of		
	California to cause birth defects. Ethyl Alcohol is included on the		
	Proposition 65 list when it is used in alcoholic beverages.		

Ethyl alcohol (64-17-5)		
U.S Massachusetts - Right To Know List		
U.S New Jersey - Right to Know Hazardous Substance List		
U.S Pennsylvania - RTK (Right to Know) List		
Sodium nitrite (7632-00-0)		
U.S Massachusetts - Right To Know List		
U.S New Jersey - Right to Know Hazardous Substance List		
U.S Pennsylvania - RTK (Right to Know) - Environmental Hazard List		
U.S Pennsylvania - RTK (Right to Know) List		
Morpholine (110-91-8)		
U.S Massachusetts - Right To Know List		
U.S New Jersey - Right to Know Hazardous Substance List		

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

U.S. - Pennsylvania - RTK (Right to Know) List

#### SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

#### **Revision Date**

**Other Information** 

: 08/21/2023

: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200

#### **GHS Full Text Phrases:**

Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Liquefied gas	Gases under pressure Liquefied gas
H280	Contains gas under pressure; may explode if heated
H319	Causes serious eye irritation

#### Party Responsible For The Preparation Of This Document

Faultless Brands: 1-816-842-1230 (for product information); 1-800-424-9300 (for emergencies)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

SDS US (GHS HazCom)