Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision Date: 08/15/2023 Date of Issue: 08/15/2023

SECTION 1: IDENTIFICATION

Product Identifier 1.1.

Product Form: Mixture

Product Names: Faultless Aerosol Spray Starches and Niagara Aerosol Spray Starches

Product Codes: 08102, 08120, 08125, 08126, 08134, 08150, 08156, 08182, 20706, 20708, 20722, 20726, 20737, 25522, 27722, 27732, 27764, 29722

*This document is intended to be used for safety in the workplace only, and is not a consumer document.

Intended Use of the Product 1.2.

Fabric finish

Name, Address, and Telephone of the Responsible Party 1.3.

Company

Faultless Brands 1025 W 8th St. Kansas City, MO 64101 USA

T: 1-816-842-1230 www.faultless.com

Emergency Telephone Number 1.4.

Emergency Number : 1-800-424-9300 (CHEMTREC)

SECTION 2: HAZARDS IDENTIFICATION

2.1. **Classification of the Substance or Mixture**

GHS-US Classification

Gases Under Pressure - Liquefied gas- H280

Full text of hazard classes and H-statements : see section 16

2.2. **Label Elements**

GHS-US Labeling

Hazard Pictograms (GHS-US)



Signal Word (GHS-US)

: Warning

Hazard Statements (GHS-US)

: H280 - Contains gas under pressure; may explode if heated.

Precautionary Statements (GHS-US) : P410+P403 - Protect from sunlight. Store in a well-ventilated place.

2.3. **Other Hazards**

Exposure may aggravate pre-existing eye, skin, or respiratory conditions. Contact with gas escaping the container can cause frostbite. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

Unknown Acute Toxicity (GHS-US) No data available 2.4.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Not applicable

3.2. Mixture

Product Identifier	% (w/w)
(CAS No) 106-97-8	1-4
(CAS No) 74-98-6	0.1 - 1
(CAS No) 75-28-5	0-0.15
(CAS No) 25322-68-3	0-0.1
	(CAS No) 106-97-8 (CAS No) 74-98-6 (CAS No) 75-28-5

SECTION 4: FIRST AID MEASURES

Description of First-aid Measures 4.1.

Version: 1.0

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). If frostbite or freezing occurs, immediately flush with plenty of lukewarm water to GENTLY warm the affected area. Do not use hot water. Do not rub affected area. Get immediate medical attention.

Inhalation: When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Obtain medical attention if irritation develops or persists. Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

Eye Contact: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

General: Contact with gas escaping the container can cause frostbite.

Inhalation: Contains a small amount of gases that are simple asphyxiants. If a large amount of gas is released in a confined space, gas could be toxic as a simple asphyxiant by displacing oxygen from the air. Prolonged exposure may cause irritation.

Skin Contact: May cause an allergic reaction in sensitive individuals. Contact with gas escaping the container can cause frostbite and freeze burns.

Eye Contact: Contact with gas escaping the container can cause frostbite, freeze burns, and permanent eye damage.

Ingestion: Not considered a potential route of exposure, but contact with gas escaping the container can cause freeze burns and frostbite.

Chronic Symptoms: None expected under normal conditions of use.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire. Water spray, dry chemical, foam, carbon dioxide.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: In accordance with subsections 31.4 and 31.5 of the UN Recommendations on the Transport of Dangerous Goods, Manual of Tests and Criteria, for Ignition distance test, and Enclosed space ignition test this material is not classified as a flammable aerosol.

Explosion Hazard: Container may explode in heat of fire.

Reactivity: Hazardous reactions will not occur under normal conditions.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Remove containers from fire area if this can be done without risk. Do not breathe fumes from fires or vapors from decomposition. Use water spray or fog for cooling exposed containers. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection. **Hazardous Combustion Products**: Thermal decomposition generates: Carbon oxides (CO, CO₂). Nitrogen oxides. Sodium oxides. Formaldehyde. Will decompose above 150 °C (> 300 °F) releasing formaldehyde vapors.

Reference to Other Sections

Refer to Section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Avoid prolonged contact with eyes, skin and clothing. Avoid breathing (vapor, mist, gas). Keep away from open flames, hot surfaces and sources of ignition.

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Emergency Procedures: Evacuate unnecessary personnel.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Evacuate unnecessary personnel, isolate, and ventilate area. Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

6.2. Environmental Precautions

Prevent entry to sewers and public waters.

6.3. Methods and Materials for Containment and Cleaning Up

For Containment: Stop leak, if possible without risk. As an immediate precautionary measure, isolate spill or leak area in all directions.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Isolate area until gas has dispersed. Absorb and/or contain spill with inert material. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Additional Hazards When Processed: Do not pressurize, cut, or weld containers. Ruptured cylinders may rocket. Contact with the product may cause cold burns or frostbite.

Precautions for Safe Handling: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid prolonged contact with eyes, skin and clothing. Avoid breathing gas.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep only in original container. Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

Incompatible Products: Strong acids, strong bases, strong oxidizers. Water reactive materials. Chlorine.

7.3. Specific End Use(s)

Fabric finish

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), or OSHA.

Polyethylene glycol (25322-68-3)		
USA AIHA	WEEL TWA (mg/m³)	10 mg/m ³ (MW>200, aerosol)
Butane (106-97-8)		
USA ACGIH	ACGIH STEL (ppm)	1000 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	1900 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	800 ppm
Propane (74-98-6)		
USA OSHA	OSHA PEL (TWA) (mg/m³)	1800 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	1800 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	1000 ppm
USA IDLH	US IDLH (ppm)	2100 ppm (10% LEL)
Isobutane (75-28-5)		
USA ACGIH	ACGIH STEL (ppm)	1000 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	1900 mg/m³

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

USA NIOSH	NIOSH REL (TWA) (ppm)	800 ppm

8.2. Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use explosion-proof equipment. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

Personal Protective Equipment: Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.



Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear protective gloves. If material is cold, wear thermally resistant protective gloves.

Eye Protection: Chemical safety goggles.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

Thermal Hazard Protection: Wear thermally resistant protective clothing.

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State	:	Liquid
Appearance	:	Clear to hazy aerosol
Odor	:	Not available
Odor Threshold	:	Not available
рН	:	6 - 7
Evaporation Rate	:	Not available
Melting Point	:	Not available
Freezing Point	:	Not available
Boiling Point	:	212 °F (100 °C)
Flash Point	:	Not available
Auto-ignition Temperature	:	Not available
Decomposition Temperature	:	Not available
Flammability (solid, gas)	:	Not available
Lower Flammable Limit	:	Not available
Upper Flammable Limit	:	Not available
Vapor Pressure	:	Not available
Relative Vapor Density at 20°C	:	Not available
Relative Density	:	Not available
Specific Gravity	:	1 g/ml
Solubility	:	Not available
Partition Coefficient: N-Octanol/Water	:	Not available
Viscosity	:	Not available
Explosive Properties	:	Contains gas under pressure; may explode if heated.
Explosion Data - Sensitivity to Mechanical Impact	:	Not expected to present an explosion hazard due to mechanical impact.
Explosion Data - Sensitivity to Static Discharge	:	Not expected to present an explosion hazard due to static discharge.

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity: Hazardous reactions will not occur under normal conditions.

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.2. Chemical Stability: Contains gas under pressure; may explode if heated.

10.3. Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

10.4. Conditions to Avoid: Direct sunlight, extremely high or low temperatures, heat, hot surfaces, sparks, open flames, incompatible materials, and other ignition sources.

10.5. Incompatible Materials: Strong acids, strong bases, strong oxidizers. Water reactive materials. Chlorine.

10.6. Hazardous Decomposition Products: None known.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects - Product

Acute Toxicity: Not classified

LD50 and LC50 Data: Not available

Skin Corrosion/Irritation: Not classified

pH: 6 - 7

Serious Eye Damage/Irritation: Not classified

pH: 6 - 7

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Teratogenicity: Not classified

Carcinogenicity: Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: Contains a small amount of gases that are simple asphyxiants. If a large amount of gas is released in a confined space, gas could be toxic as a simple asphyxiant by displacing oxygen from the air. Prolonged exposure may cause irritation.

Symptoms/Injuries After Skin Contact: May cause an allergic reaction in sensitive individuals. Contact with gas escaping the container can cause frostbite and freeze burns.

Symptoms/Injuries After Eye Contact: Contact with gas escaping the container can cause frostbite, freeze burns, and permanent eye damage.

Symptoms/Injuries After Ingestion: Not considered a potential route of exposure, but contact with gas escaping the container can cause freeze burns and frostbite.

Chronic Symptoms: None expected under normal conditions of use.

11.2. Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Polyethylene glycol (25322-68-3)		
LD50 Oral Rat	47000 mg/kg	
LD50 Dermal Rabbit	> 20 ml/kg	
Butane (106-97-8)		
LC50 Inhalation Rat	30957 mg/m ³ (Exposure time: 4 h)	
Propane (74-98-6)		
LC50 Inhalation Rat	658 mg/l/4h	
Isobutane (75-28-5)		
LC50 Inhalation Rat	658 mg/l/4h	
LC50 Inhalation Rat	11000 ppm	

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General: Not classified.

12.2. Persistence and Degradability

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Faultless Brands Aerosol Spray Starches		
Persistence and Degradability	Not established.	
12.3. Bioaccumulative Potential		
Faultless Brands Aerosol Spray Starches		
Bioaccumulative Potential	Not established.	
Butane (106-97-8)		
Log Pow	2.89	
Propane (74-98-6)		
Log Pow	2.3	
Isobutane (75-28-5)		
BCF Fish 1	1.57 - 1.97	
Log Pow	2.88 (at 20 °C)	

12.4. Mobility in Soil Not available

12.5. Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste Disposal Recommendations: Dispose of contents/container in accordance with local, regional, national, and international regulations.

Additional Information: Container may remain hazardous when empty. Continue to observe all precautions. Do not puncture or incinerate container.

Ecology - Waste Materials: Avoid release to the environment.

SECTION 14: TRANSPOR	T INFORMATION
14.1. In Accordance wi	ith DOT
Proper Shipping Name	: AEROSOLS non-flammable, (each not exceeding 1 L capacity)
Hazard Class	: 2.2
Identification Number	: UN1950
Label Codes	: 2.2
ERG Number	: 126
Shipped under 49 CFR, Packa	ging Exception 173.306 - Consumer Commodities, Limited Quantities of Compressed Gases
14.2. In Accordance wi	ith IMDG
Proper Shipping Name	: AEROSOLS non-flammable, (each not exceeding 1 L capacity)
Hazard Class	: 2
Division	: 2.2
Identification Number	: UN1950
Label Codes	: 2.2
EmS-No. (Fire)	: F-D 🤇 🔪
EmS-No. (Spillage)	: S-U
14.3. In Accordance wi	ith IATA
Proper Shipping Name	: AEROSOLS, NON-FLAMMABLE
Identification Number	: UN1950
Hazard Class	: 2 < Y >
Label Codes	: 2.2
Division	: 2.2
ERG Code (IATA)	: 2L
SECTION 15. REGULATO	

SECTION 15: REGULATORY INFORMATION

15.1. US Federal Regulations

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Faultless Brands Aerosol Spray Starches

Faultiess Branus Aerosol Spray Starches		
SARA Section 311/312 Hazard Classes	Sudden release of pressure hazard	
Polyethylene glycol (25322-68-3)		
Listed on the United States TSCA (Toxic Substances Control Act	inventory	
Butane (106-97-8)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Propane (74-98-6)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Isobutane (75-28-5)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
15.2. US State Regulations		
Butane (106-97-8)		
U.S Massachusetts - Right To Know List		
U.S New Jersey - Right to Know Hazardous Substance List		
U.S Pennsylvania - RTK (Right to Know) List		
Propane (74-98-6)		

U.S. - Massachusetts - Right To Know List

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

Isobutane (75-28-5)

U.S. - Massachusetts - Right To Know List

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date	: 08/15/2023
Other Information	: This document has been prepared in accordance with the SDS
	requirements of the OSHA Hazard Communication Standard 29 CFR
	1910.1200
GHS Full Taxt Phrases	

GHS Full Text Phrases:

Liquefied gas	Gases under pressure Liquefied gas
H280	Contains gas under pressure; may explode if heated

Party Responsible For The Preparation Of This Document

Faultless Brands: 1-816-842-1230 (for product information); 1-800-424-9300 (for emergencies)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

SDS US (GHS HazCom)