

Silver Satin 3

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations
Revision Date: 04/12/2016 Date of issue: 04/12/2016

Version: 2.0

SECTION 1: IDENTIFICATION

1.1. Product Identifier

Product Form: Mixture

Product Name: Silver Satin 3

Product Code: 16200, 16205

*This document is intended to be used for safety in the workplace only, and is not a consumer document.

1.2. Intended Use of the Product

Laundry sour

1.3. Name, Address, and Telephone of the Responsible Party

Faultless Starch/ Bon Ami Co.

1025 W 8th St.

Kansas City, MO 64101 USA

T: 1-816-842-1230

www.faultless.com

1.4. Emergency Telephone Number

Emergency Number : 1-800-424-9300 (CHEMTREC)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

GHS-US classification

Acute Tox. 3 (Oral) H301

Acute Tox. 3 (Dermal) H311

Acute Tox. 3 (Inhalation:dust,mist) H331

Aquatic Acute 3 H402

Full text of hazard classes and H-statements : see section 16

2.2. Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US) :



GHS06

Signal Word (GHS-US) :

Danger

Hazard Statements (GHS-US) :

H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled.
H402 - Harmful to aquatic life.

Precautionary Statements (GHS-US) :

P261 - Avoid breathing vapors, mist, or spray.
P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P271 - Use only outdoors or in a well-ventilated area.
P273 - Avoid release to the environment.
P280 - Wear protective gloves, protective clothing, and eye protection.
P301+P310 - If swallowed: Immediately call a poison center or doctor.
P302+P352 - If on skin: Wash with plenty of water.
P304+P340 - If inhaled: Remove person to fresh air and keep at rest in a position comfortable for breathing.
P311 - Call a poison center or doctor.
P312 - Call a poison center or doctor if you feel unwell.
P321 - Specific treatment (see section 4).
P330 - Rinse mouth.
P361 - Take off immediately all contaminated clothing.
P363 - Wash contaminated clothing before reuse.

Silver Satin 3

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P405 - Store locked up.

P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.

2.3. Other Hazards

Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions.

2.4. Unknown Acute Toxicity (GHS-US) No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Not applicable

3.2. Mixture

Name	Product Identifier	% (w/w)
Silicate(2-), hexafluoro-, disodium	(CAS No) 16893-85-9	60 - 70
Tinopal CBS	(CAS No) 27344-41-8	0.1 - 1

The specific chemical identity and/or exact percentage of composition have been withheld as a trade secret [29 CFR 1910.1200]. A range of concentration as prescribed by the Controlled Products Regulations has been used where necessary, due to varying composition.

SECTION 4: FIRST AID MEASURES

4.1. Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If exposed or concerned: seek immediate medical attention.

Inhalation: First, take proper precautions to ensure your own safety before attempting rescue (e.g. wear appropriate respiratory protective equipment, use the buddy system), then remove the exposed person to fresh air. Keep at rest in a position comfortable for breathing. Seek immediate medical advice.

Skin Contact: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. Seek medical attention.

Eye Contact: Rinse with plenty of water immediately. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical attention immediately.

Ingestion: Do not induce vomiting. Rinse mouth. Seek medical attention.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

General: Toxic if swallowed, in contact with skin or if inhaled.

Inhalation: Toxic if inhaled. Inhalation of this material can cause serious health effects in small amounts, leading to unconsciousness and death.

Skin Contact: This material is toxic in small amounts through skin contact, and can cause adverse health effects or death. This material may be absorbed through the skin and eyes.

Eye Contact: May cause slight irritation to eyes. May be absorbed through the eyes and have toxic effects.

Ingestion: This material is toxic in small amounts orally, and can cause adverse health effects or death.

Chronic Symptoms: None expected under normal conditions of use.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If you feel unwell, seek medical advice (show the label where possible).

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Dry sand. dry chemical powder. Carbon dioxide (CO₂).

Unsuitable Extinguishing Media: May react with water, metals to release explosive hydrogen gas. Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not considered flammable.

Explosion Hazard: Product is not explosive. In the presence of water, contact with metals may produce hydrogen which may form explosive mixtures with air.

Reactivity: Hazardous reactions are not expected to occur under normal conditions.

Silver Satin 3

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire. Under fire conditions, hazardous fumes will be present.

Firefighting Instructions: In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion. Use water spray or fog for cooling exposed containers. Do not allow run-off from firefighting to enter drains or water courses. Do not get water inside containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Thermal decomposition generates: Carbon oxides (CO, CO₂). Sodium oxides. Hydrogen chloride gas. Silicon Tetrafluoride. Fluosilicates. .

Other Information: Do not allow run-off from fire fighting to enter drains or water courses.

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Avoid generating dust. Do not get in eyes, on skin, or on clothing. Do not breathe dust.

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel. Evacuate unnecessary personnel.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area.

6.2. Environmental Precautions

Prevent entry to sewers and public waters. Contact competent authorities after a spill.

6.3. Methods and Material for Containment and Cleaning Up

For Containment: Contain solid spills with appropriate barriers and prevent migration and entry into sewers or streams. As an immediate precautionary measure, isolate spill or leak area in all directions.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Recover the product by vacuuming, shoveling or sweeping. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

6.4. Reference to Other Sections

See Section 8, Exposure Controls and Personal Protection. See Section 13, Disposal Considerations.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Additional Hazards When Processed: Any proposed use of this product in elevated-temperature processes should be thoroughly evaluated to assure that safe operating conditions are established and maintained. Avoid dust production.

Precautions for Safe Handling: Do NOT get in eyes, on skin or on clothing. Do not breathe dust. Use only outdoors or in a well-ventilated area.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations. Avoid creating or spreading dust.

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store in a dry, cool place. Store locked up.

Incompatible Materials: Reducing agents. Water, humidity. Strong acids, strong bases, strong oxidizers.

7.3. Specific End Use(s)

Laundry sour

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government.

Silver Satin 3

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

8.2. Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Provide adequate ventilation to minimize dust concentrations. Ensure all national/local regulations are observed. Gas detectors should be used when toxic gases may be released.

Personal Protective Equipment: Protective goggles. Protective clothing. Gloves. Insufficient ventilation: wear respiratory protection.



Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Impermeable protective gloves.

Eye Protection: Chemical safety goggles.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

Environmental Exposure Controls: Do not allow the product to be released into the environment.

Consumer Exposure Controls: Do not eat, drink or smoke during use

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State	: Solid
Appearance	: White
Odor	: Pleasant
Odor Threshold	: Not available
pH	: 2.8 - 3.8 (1% solution)
Evaporation Rate	: Not available
Melting Point	: Not available
Freezing Point	: Not available
Boiling Point	: Not available
Flash Point	: Not available
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not available
Relative Vapor Density at 20 °C	: Not available
Relative Density	: Not available
Specific Gravity	: Not available
Solubility	: 60 - 70% in cold water
Partition Coefficient: N-Octanol/Water	: Not available
Viscosity	: Not available
Explosion Data – Sensitivity to Mechanical Impact	: Not expected to present an explosion hazard due to mechanical impact
Explosion Data – Sensitivity to Static Discharge	: Not expected to present an explosion hazard due to static discharge

Silver Satin 3

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

SECTION 10: STABILITY AND REACTIVITY

- 10.1. Reactivity:** Hazardous reactions are not expected to occur under normal conditions.
- 10.2. Chemical Stability:** Stable under recommended handling and storage conditions (see section 7).
- 10.3. Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.
- 10.4. Conditions to Avoid:** Direct sunlight, extremely high or low temperatures, and incompatible materials.
- 10.5. Incompatible Materials:** Reducing agents. Water, humidity. Strong acids, strong bases, strong oxidizers.
- 10.6. Hazardous Decomposition Products:** Thermal decomposition generates: Carbon oxides (CO, CO₂). Sodium oxides. Hydrogen chloride gas. Silicon Tetrafluoride. Fluosilicates. Toxic fumes.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects - Product

Acute Toxicity: Oral: Toxic if swallowed. Dermal: Toxic in contact with skin. Inhalation:dust,mist: Toxic if inhaled.

LD50 and LC50 Data:

Silver Satin 3	
ATE US (oral)	205.42 mg/kg body weight
ATE US (dermal)	493.02 mg/kg body weight
ATE US (dust, mist)	0.82 mg/l/4h

Skin Corrosion/Irritation: Not classified

pH: 2.8 - 3.5 (1% solution)

Serious Eye Damage/Irritation: Not classified

pH: 2.8 - 3.5 (1% solution)

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Teratogenicity: Not classified

Carcinogenicity: Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: Toxic if inhaled. Inhalation of this material can cause serious health effects in small amounts, leading to unconsciousness and death.

Symptoms/Injuries After Skin Contact: This material is toxic in small amounts through skin contact, and can cause adverse health effects or death. This material may be absorbed through the skin and eyes.

Symptoms/Injuries After Eye Contact: May cause slight irritation to eyes. May be absorbed through the eyes and have toxic effects.

Symptoms/Injuries After Ingestion: This material is toxic in small amounts orally, and can cause adverse health effects or death.

Chronic Symptoms: None expected under normal conditions of use.

11.2. Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Tinopal CBS (27344-41-8)	
LD50 Oral Rat	5580 mg/kg
LD50 Dermal Rat	> 2000 mg/kg
LC50 Inhalation Rat	3.6 mg/l/4h
LC50 Inhalation Rat	3.66 mg/l/4h
Silicate(2-), hexafluoro-, disodium (16893-85-9)	
LD50 Oral Rat	125 mg/kg
LC50 Inhalation Rat	1.814 mg/l/4h
Silicate(2-), hexafluoro-, disodium (16893-85-9)	
IARC Group	3

Silver Satin 3

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General: Harmful to aquatic life.

Tinopal CBS (27344-41-8)	
LC50 Fish 1	76 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [static])
EC50 Daphnia 1	1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 Other Aquatic Organisms 2	10 (10.0 - 11.0) mg/l (Exposure time: 96 h - Species: Desmodesmus subspicatus)
NOEC (acute)	1.37 mg/kg (Exposure time: 14 Days - Species: Eisenia foetida [soil dry weight])
Silicate(2-), hexafluoro-, disodium (16893-85-9)	
LC50 Fish 1	65 mg/l (Exposure time: 96 h - Species: Poecilia reticulata [static])

12.2. Persistence and Degradability

Silver Satin 3	
Persistence and Degradability	Not established.

12.3. Bioaccumulative Potential

Silver Satin 3	
Bioaccumulative Potential	Not established.
Tinopal CBS (27344-41-8)	
BCF Fish 1	< 1

12.4. Mobility in Soil Not available

12.5. Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Sewage Disposal Recommendations: This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations

Additional Information: Container may remain hazardous when empty. Continue to observe all precautions.

Ecology – Waste Materials: This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

SECTION 14: TRANSPORT INFORMATION

14.1. In Accordance with DOT

Proper Shipping Name : SODIUM FLUOROSILICATE MIXTURE
Hazard Class : 6.1
Identification Number : UN2674
Label Codes : 6.1
Packing Group : III
ERG Number : 151



14.2. In Accordance with IMDG

Proper Shipping Name : SODIUM FLUOROSILICATE MIXTURE
Hazard Class : 6.1
Division : 6.1
Identification Number : UN2674
Packing Group : III
Label Codes : 6.1
EmS-No. (Fire) : F-A
EmS-No. (Spillage) : S-A



Silver Satin 3

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

14.3. In Accordance with IATA

Proper Shipping Name : SODIUM FLUOROSILICATE MIXTURE
Packing Group : III
Identification Number : UN2674
Hazard Class : 6.1
Label Codes : 6.1
Division : 6.1
ERG Code (IATA) : 6L



14.4. In Accordance with TDG

Proper Shipping Name : SODIUM FLUOROSILICATE MIXTURE
Packing Group : III
Hazard Class : 6.1
Identification Number : UN2674
Label Codes : 6.1



SECTION 15: REGULATORY INFORMATION


15.1. US Federal Regulations

Silver Satin 3	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard
Tinopal CBS (27344-41-8)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Silicate(2-), hexafluoro-, disodium (16893-85-9)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

15.2. US State Regulations

Tinopal CBS (27344-41-8)	
U.S. - Texas - Effects Screening Levels - Long Term	
U.S. - Texas - Effects Screening Levels - Short Term	
Silicate(2-), hexafluoro-, disodium (16893-85-9)	
RTK - U.S. - Massachusetts - Right To Know List	
RTK - U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Texas - Effects Screening Levels - Long Term	
U.S. - Texas - Effects Screening Levels - Short Term	

15.3. Canadian Regulations

Silver Satin 3	
WHMIS Classification	Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects
	
Tinopal CBS (27344-41-8)	
Listed on the Canadian DSL (Domestic Substances List)	
Listed on the Canadian IDL (Ingredient Disclosure List)	
IDL Concentration 0.1 %	
WHMIS Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects
Silicate(2-), hexafluoro-, disodium (16893-85-9)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

Silver Satin 3

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date : 04/12/2016

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 3 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
H301	Toxic if swallowed
H311	Toxic in contact with skin
H331	Toxic if inhaled
H402	Harmful to aquatic life

Party Responsible for the Preparation of This Document

Faultless Starch/ Bon Ami Co.: 1-816-842-1230 (for product information); 1-800-424-9300 (for emergencies)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

NA GHS SDS